



NOTES:
 1) WHEN MOUNTING IN A RACK CABINET, KEEP TOP VENTS CLEAR FOR OPTIMAL CPU COOLING. IF NECESSARY, USE OF A 1/2U RACK SPACER ABOVE IS RECOMMENDED.

2) SOME OPTIONAL PARTS ARE SHOWN. STANDARD CHASSIS SUPPORTS TWO FULL-HEIGHT CARDS UP TO 10" LONG AND ONE 2.5" DRIVE BAY. OPTIONAL BRACKETS ALLOW EITHER TWO ADDITIONAL 2.5" DRIVE BAYS, OR A THIRD CARD UP TO 6" LONG. THE THIRD CARD CAN BE PCI-32 OR PCI EXPRESS x1

TOLERANCES UNLESS NOTED	MATERIAL
X.XX ±0.12	-
X.X ±0.25	-
X ±0.50	-
ANGULAR ± 1°	-

FINISH	PROJECTION	UNITS
-		mm

GT GENERAL TECHNICS, INC.
 INDUSTRIAL COMPUTER SYSTEMS

PROPRIETARY NOTICE
 This drawing contains proprietary information of GENERAL TECHNICS INC. Any duplication or use of this drawing, in whole or in part, without a written consent from GENERAL TECHNICS INC. is strictly prohibited.

APP	DGN	DRW
-	-	JAMES CETRANGELD

TITLE	GT CID	DWG NO	REV
1.5U MICRO-ATX CHASSIS	-	GT0152-000	02

SCALE: 1:1
 SHEET: 1 OF 1
 SIZE: C