



## PT1510MX 15" Touchscreen LCD Monitor

Essential Performance. Resistive Touch. Great Value.

The cost-effective PT1510MX 15" touchscreen monitor is perfect for use in retail, point-of-sale and hospitality applications. Available in black or white. Easily integrated with a variety of POS, thin client or PC systems, the touch LCD features 5-wire resistive touchscreen and dual RS-232/USB touchscreen interface. The touchscreen monitor comes standard with a deskstand, but is also compatible with other mounting options using the 75mm VESA standard hole pattern on the back of the monitor.

The PT1510MX includes Planar's industry leading 3-year Customer First™ Warranty featuring Free 2-Day Advance Replacement. The result is an exceptional durable touchscreen monitor and an excellent value.

### Features:

Perfect for kiosk integrators, VARs and OEMs in retail, POS or hospitality applications

5-wire resistive touchscreen for indoor environments

Dual Serial/USB touchscreen interface

Recognizes touch input from stylus, finger, gloved hand, pen or tool

Compatible with mounting options that use the 75 mm VESA standard

Customer First™ Warranty featuring 2-Day Advance Replacement

Available in black or white

### Specifications:

Product Name	PT1510MX
Planar Part Number	997-3198-00 (Black), 997-3394-00 (White)
Viewable Size	15 inch diagonal
Touchscreen Type	5-wire resistive touchscreen
Touchscreen Interface	Dual Serial and USB
Transmissivity	78% (typical)
Contrast Ratio (Typical)	500:1
Viewing Angle (Typical)	140° Horizontal and 125° Vertical
Response Time (Typical)	8 ms
Brightness (w/touchscreen)	190 cd/m <sup>2</sup>
Brightness (w/o)	250 cd/m <sup>2</sup>

Brightness (w/o touchscreen)	200 cd/m <sup>2</sup>
Display Type	LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1024 x 768
Tilt Range	-3° to +25°
Palette	16.7 million colors
Pixel Pitch	0.297 mm
Refresh Rate	56 to 75 Hz (60 Hz recommended)
Dimensions (W x H x D)	15.9" x 15.3" x 7.5" (403.9 mm x 388.6 mm x 190.5 mm)
Dimensions without Stand	15.9" x 12.3" x 2.2" (403.9 mm x 312.4 mm x 55.9 mm)
Display Weight	With Stand: 10.4 lbs (4.7 kg) (net), 14.9 lbs (6.8 kg) (shipping)
Display Weight (w/o stand)	7.9 lbs (4.7 kg)
Panel Depth	2.2"
Video Inputs	Analog
Audio Output	Integrated stereo speakers with 1W/channel
Compatibility	Windows® Vista, XP, XP Embedded, 2000
External Connections	DC power-in barrel connector, D-sub 15 pin, Audio In connector, Serial RS-232 connector, USB connector
Power Supply	External
Power Requirements	100-240 VAC, 50/60Hz
Power Consumption	30W (5W standby)
VESA Compatible/Location	Built-in 75 mm VESA, monitor back
Service and Support	3-Year Customer First™ warranty featuring FREE 2-Day Advance Replacement for three full years
Options / Features	Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® security lock function, Built-in 75 mm VESA, back
Product Approvals	UL/cUL, FCC-B, CE-B, TUV, RoHS, CCC, China RoHS